

# High Pressure Cleaner

## KD1340



Type	KD1340-Standard		KD1340-Premium
Voltage	3/PE/AC/50Hz/400V	<ul style="list-style-type: none"> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>35l Cleaning-Detergent tank</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>Hose-Reel</li> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>25l Water-Storage tank</li> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Operating pressure	30-170bar/3-17MPa		
Max. pressure	190bar/19MPa		
Discharge capacity	300-1300l/h		
Nozzle size	070		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	7,4kW/13,1A		
Electrical protection	3x16A slow		
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		98x62x100cm/109x63x112cm	98x62x100cm/109x63x112cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

Art.No.	552003	552004
---------	--------	--------